



POWER SYNT 4T

SAE 10W/50 JASO MA2

Fully synthetic high-performance engine oil for 4-stroke hypersport motorcycles

Description

Fully synthetic high-performance 4-stroke engine oil, specially developed for demanding use in hypersport motorcycles with powerful engines. These lubrications provide engines, gearboxes and clutches with optimum protection over the entire range of applications. JASO MA2 approval guarantees the fault-free functioning of wet multi-disc clutches.

Advantages

- fully synthetic
- serious power delivery
- Racing quality
- optimum wear protection
- extremely good thermal and shear stability
- Catalytic converter tested
- ideal for wet multi-disc clutches (JASO MA2 approval)

Field of application

Available in three different viscosities, MOTOREX POWER SYNT 4T is specially designed for sporting use. Ideal for high-performance motorcycles with wet multi-disc clutches. Also meets the highest manufacturer's specifications.

Specifications

JASO MA-2; API SM; API SL; API SJ; API SH; API SG



Technical data

Properties	Unit	Test according to	Values
Colour			brown
Density at 20 °C	g/cm ³	ASTM D4052	0.861
Viscosity at 40 °C	mm ² /s	DIN 51562-1	114.8
Viscosity at 100 °C	mm ² /s	DIN 51562-1	17.5
Viscosity index		DIN ISO 2909	168
Viscosity according to HTHS at 150 °C	mPa·s	CEC-L-36 A-97	≥3.5
Pourpoint	°C	ASTM D5950	-48
Flash point C.O.C.	°C	DIN EN ISO 2592	≥200
CCS at	°C / mPa·s	ASTM D 5293	-25 / 4550
Sulphate residue content	%	DIN EN ISO 6245	1.2
Phosphor	%		0.11
Sulfur	%		0.30
NOACK	%	CEC L-40-A-93	5.1
TBN	mg KOH/g	DIN ISO 3771	9.6

European waste code: 13 02 06 / Water hazard class: 1

The above information corresponds to the current state of our knowledge. We reserve the right to make changes. The performance characteristics indicated are based on testing and production tolerances standard in this industry. A safety data sheet is available.

