

# LEGEND 4T

## SAE 20W/50

High-quality mineral-oil-based engine oil for 4-stroke motorcycles with separate engine and gearbox lubrication

### Description

MOTOREX LEGEND 4T is a special engine oil for motorcycles with powerful 4-stroke engines where the engine and gearbox are lubricated separately. Thanks to the selection of base oils and additives specially adapted for this engine type, this engine oil provides optimum protection against wear and high temperature stability.

### Advantages

- Good wear protection
- High thermal stability
- Optimum oil film, even at high temperatures
- Ideal for high-capacity two-cylinder engines

### Field of application

MOTOREX LEGEND 4T SAE 20W/50 has been specially developed for use in large two-cylinder engines. Ideal for air-cooled engines as well.

### Specifications

API SJ, SH, SG/CF,  
ACEA A3/B3 -04

### Technical data

Properties	Unit	Test according to	Values
Viscosity class		SAE J 300	20W/50
Colour		DIN ISO 2049	brown
Density at 20 °C	g/ml	ASTM D 4052	0.885
Viscosity at 40 °C	mm <sup>2</sup> /s	DIN 51562-1	169
Viscosity at 100 °C	mm <sup>2</sup> /s	DIN 51562-1	19
Viscosity according to HTSH at 150 °C	mPa·s	CEC-L-36-A-97	≥3.5
CCS at -15 °C	mPa s	ASTM D 5293	8926
Viscosity index		DIN ISO 2909	121
Pourpoint	°C	ASTM D 5950	-24
Flash point	°C	DIN EN ISO 2592	≥200
NOACK	% by weight	CEC-L-40-A-93	6.8

Water hazard class: WGK 1  
Disposal code: EWC 130 205

The above information is subject to change without prior notice, although it is in accordance with current standards. Performance characteristics indicated are based on usual tolerances which occur during measuring and production using the latest technology. A safety data sheet is available.

